

4 Pack Polyurethane Nylon Plate 100mm - Various Configurations

Product code: BZMM100NP/SETS

4 pack pressed steel top plate fixing fitted with a Polyurethane wheel with a Plain Bore. Wheel diameter 100mm, tread width 30mm, overall height 128mm. Top plate 105mm x 85mm, hole centres 80mm x 60mm. Load capacity 180kg per castor / 540kg Total set load.



Diameter (mm)	100
Fixing Option	Plate
Castor Type	Fixed, Swivel, Swivel with Total Lock Brake
Height (mm)	128
Bearing Type	Plain
Swivel Radius (mm)	85 Swivel / 118 Braked
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane on Nylon Rim / 96 Shore A
Fork Thickness (mm)	2
Temperature Resistance	-20 °C TO +70 °C
To Suit Fixing Bolt (mm)	8
Tread (mm)	30
Plate Size (mm)	105 X 85
Hole Centres (mm)	80 X 60
Top Plate Thickness (mm)	2
Configuration	2 x Fixed + 2 x Braked, 2 x Swivel + 2 x Braked, 2 x Swivel + 2 x Fixed
Load Capacity (kg)	540 Per Set