

4 Pack Polyurethane Nylon Plate 150mm - Various Configurations

Product code: BZMM150NP/SETS

4 pack pressed steel 2 x swivel and 2 x swivel with total lock brake castor plate fixing fitted with a Polyurethane wheel with a Plain Bore. Wheel diameter 150mm, tread width 40mm, overall height 190mm. Top plate 135mm x 110mm, hole centres 105mm x 80mm. Load capacity 400kg per castor / 1200kg Total set load.



Diameter (mm)	150
Fixing Option	Plate
Castor Type	Fixed, Swivel, Swivel with Total Lock Brake
Height (mm)	190
Bearing Type	Plain
Swivel Radius (mm)	128 Swivel / 167 Braked
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane on Nylon Rim / 96 Shore A
Fork Thickness (mm)	3
Temperature Resistance	-20 °C TO +70 °C
To Suit Fixing Bolt (mm)	10
Tread (mm)	40
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80
Top Plate Thickness (mm)	3
Configuration	2 x Fixed + 2 x Braked, 2 x Swivel + 2 x Braked, 2 x Swivel + 2 x Fixed
Load Capacity (kg)	1050 Per Set