

## Black Rubber Tyred Castor 250mm 1000kg Load

**Product code: VSP250HR2PBLK**

Fabricated zinc-plated swivel castor with plate fixing fitted with a black elastic rubber tyred on a steel disc-centered wheel with ball bearings. Wheel diameter 250mm, tread width 75mm, overall height 316mm, plate size 170mm x 135mm, hole centre's 140mm x 105mm. Load capacity 1000kg at 4kph, 800kg at 10kph and 400kg at 20kph \*\* FOR INTERNAL AND EXTERNAL TOWING USE \*\*



Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	316
Plate Size (mm)	170 x 135
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	m12
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	-20 °C TO +60 °C
Top Plate Thickness (mm)	10
Fork Thickness (mm)	6
Swivel Radius (mm)	200
Load Capacity (kg)	1000
Tread (mm)	75

## BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

