

Black Soft Elastic Rubber on Aluminium Plate Swivel Castor Brake 250mm 500kg Load

Product code: BZK250SRERBJSWB

Fabricated steel swivel castor with a top plate fixing fitted with a ergonomic black high elastic natural 55 shore A round profile rubber tyre aluminium centred wheel with a ball journal bearings and a total lock brake. Wheel diameter 250mm, tread width 55mm, overall height 300mm, top plate 150mm x 110mm, hole centres 105mm x 80mm or 121mm x 59mm. Load capacity 500kg at 4kph, 200 at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC. ** FOR INTERNAL AND EXTERNAL TOWING USE **



Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	300
Plate Size (mm)	150 x 110
Hole Centres (mm)	105/121 x 80/59
To Suit Fixing Bolt (mm)	12
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	7.5
Fork Thickness (mm)	6
Swivel Radius (mm)	197
Load Capacity (kg)	500
Tread (mm)	55

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821 VAT Reg: GB572705729





(

UKAS

auvo

ISO 14001 CERTIFIED