

## Black Soft Elastic Rubber Plate Swivel Castor 150mm 270kg Load

**Product code: BZSAB150SRERBJ**

Fabricated yellow ROHS zinc plated swivel castor with plate fixing fitted with a black high elastic natural 55 shore A round profile rubber aluminium centred wheel with ball bearings. Wheel diameter 150mm, tread width 47mm, overall height 200mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 270kg at 4kph and 100kg at 10kph. - At 6 kph speed, the load of each wheel is advised to be 80% of the load at 4kph - At 10 kph speed, the load of each wheel is advised to be 55% of the load at 4 kph. .REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC, also available with flat tread details on request  
**\*\* FOR INTERNAL AND EXTERNAL TOWING USE \*\***



Diameter (mm)	150
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	200
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6
Swivel Radius (mm)	130
Load Capacity (kg)	250
Tread (mm)	47

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

