

Black Soft Elastic Rubber Plate Swivel Castor Brake 100mm 150kg Load

Product code: BZMM100SRERBJSWB

Pressed steel swivel castor top plate fixing fitted with a a black ergonomic round profile high elastic natural 55 shore A rubber tyred aluminium centred wheel with ball bearings and a total lock brake. Wheel diameter 100mm, tread width 40mm, overall height 128mm, top plate 105mm x 85mm, hole centres 80mm x 60mm. Load capacity 150kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



| | |
|--------------------------|--|
| Diameter (mm) | 100 |
| Castor Type | Swivel with Total Lock Brake |
| Fixing Option | Plate |
| Height (mm) | 128 |
| Wheel Material | Rubber on Aluminium |
| Colour / Shore Hardness | Black Ergonomic Rubber on Aluminium Rim / 55 Shore A |
| Temperature Resistance | -30 °C TO +80 °C |
| Bearing Type | Ball |
| Load Capacity (kg) | 150 |
| Tread (mm) | 40 |
| Swivel Radius (mm) | 118 |
| Plate Size (mm) | 105 X 85 |
| Hole Centres (mm) | 80 X 60 |
| Top Plate Thickness (mm) | 2.5 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

