

Black Soft Elastic Rubber Plate Swivel Castor Brake 200mm 380kg Load

Product code: BZSAB200SRERBJSWB

Fabricated zinc plated swivel castor with plate fixing fitted with a black high elastic natural 55 shore A round profile rubber aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 250mm, plate size 138mm x 110mm, hole centrtes 105mm x 80mm/75mm. Load capacity 380kg at 4kph and 152kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC, ** FOR INTERNAL AND EXTERNAL TOWING USE **



Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	250
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6
Swivel Radius (mm)	155
Load Capacity (kg)	380
Tread (mm)	50

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821 VAT Reg: GB572705729





UKAS

auvo

ISO 14001 CERTIFIED