

## Black Soft Elastic Rubber Plate Swivel Castor Brake 250mm 500kg Load

**Product code: BZSAB250SRERBJSWB**



Fabricated zinc plated swivel castor with plate fixing fitted with a black high elastic natural 55 shore A round profile rubber aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 250mm, tread width 55mm, overall height 300mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 500kg at 4kph and 200kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC, \*\* FOR INTERNAL AND EXTERNAL TOWING USE \*\*

Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	300
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6
Swivel Radius (mm)	200
Load Capacity (kg)	500
Tread (mm)	50