



## Black Soft Elastic Speed Rubber on Aluminium Plate Swivel Castor 150mm 250kg Load

Product code: BZSPH150SRERBJ

Pressed steel swivel castor with a top plate fixing fitted with a black high elastic natural 55 shore A round profile rubber tyre wheel aluminium centre with ball bearings. Wheel diameter 150mm, tread width 47mm, overall height 190mm, top plate 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 250kg at 4kph and 100kph at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC \*\* FOR INTERNAL TOWING ONLY \*\*



| Diameter (mm)            | 150  |
|--------------------------|--|
| Castor Type              | Swivel   |
| Fixing Option            | Plate  |
| Height (mm)              | 190  |
| Wheel Material           | Rubber on Aluminium                                  |
| Colour / Shore Hardness  | Black Ergonomic Rubber on Aluminium Rim / 55 Shore A |
| Temperature Resistance   | -30 °C TO +80 °C                                     |
| Bearing Type             | Ball   |
| Load Capacity (kg)       | 250  |
| Tread (mm)               | 47   |
| Swivel Radius (mm)       | 128  |
| Plate Size (mm)          | 135 x 110  |
| Hole Centres (mm)        | 105 x 80/75  |
| Top Plate Thickness (mm) | 5  |
| Fork Thickness (mm)      | 5  |
| To Suit Fixing Bolt (mm) | 10   |





