



## Black Soft Elastic Speed Rubber on Aluminium Plate Swivel Castor Brake 160mm 300kg Load

Product code: BZSPH160SRERBJSWB

Pressed steel swivel castor with a top plate fixing fitted with a black high elastic natural 55 shore A rubber tyre wheel aluminium centre with ball bearings and total lock brake. Wheel diameter 160mm, tread width 50mm, overall height 195mm, top plate 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 300kg at 4kph and 120kph at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC \*\*FOR INTERNAL TOWING ONLY\*\*



Diameter (mm)	160
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	195
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Ergonomic Rubber on Aluminium Rim / 55 Shore A
Temperature Resistance	-30 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	300
Tread (mm)	50
Swivel Radius (mm)	167
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80/75
Top Plate Thickness (mm)	5
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	10





