

Elastic Rubber Cast Iron Plate Swivel Castor Brake 200mm 500kg Load

Product code: BZSAB200CUBJSWB



Fabricated yellow ROHS zinc plated swivel castor with plate fixing fitted with a black elastic rubber tyred on a cast iron centred wheel centred wheel with ball bearings and a total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 250mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 500kg, - At 6 kph speed, the load of each wheel is advised to be 80% of the load at 4kph - At 10 kph speed, the load of each wheel is advised to be 55% of the load at 4 kph. - At 16 kph speed, the load of each wheel is advised to be 45% of the load at 4kph. - At 20 kph speed, the load of each wheel is advised to be 35% of the load at 4 kph. - No data for elastic rubber wheel over 20 kph.

**** FOR INTERNAL AND EXTERNAL TOWING USE ****

| | |
|--------------------------|--|
| Diameter (mm) | 200 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Bearing Type | Ball |
| Height (mm) | 250 |
| Plate Size (mm) | 138 x 110 |
| Hole Centres (mm) | 105 x 80 |
| To Suit Fixing Bolt (mm) | 10 |
| Wheel Material | Rubber on Cast Iron |
| Colour / Shore Hardness | Black Elastic Rubber on Cast Iron Rim / 65 Shore A |
| Temperature Resistance | -20 °C TO +60 °C |
| Top Plate Thickness (mm) | 8 |
| Fork Thickness (mm) | 6 |
| Swivel Radius (mm) | 155 |
| Load Capacity (kg) | 500 |
| Tread (mm) | 50 |