

Elastic Rubber on Aluminium Plate Swivel Castor 150mm 700kg Load

Product code: 2BZQ150ERBJ



Fabricated swivel castor with a flat plate fixing fitted with 2 x black high elastic natural 65 shore A rubber tyred on aluminium centred wheels with ball bearings. Wheel diameter 150mm, tread width 2 x 50mm, overall height 264mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 700kg at 4kph and 280kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC ** FOR INTERNAL AND EXTERNAL TOWING USE **

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
Height (mm)	212
Swivel Radius (mm)	140
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	"-30 °C TO +80 °C
Tread (mm)	2 x 50
Load Capacity (kg)	700
Top Plate Thickness (mm)	12
Fork Thickness (mm)	8

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729