

## Elastic Rubber on Aluminium Plate Swivel Castor 160mm 400kg Load

**Product code: BZMJ160ERBJ**

Fabricated white zinc ROHS plated swivel castor with top plate fixing fitted with a black high elastic natural 65 shore A rubber tyre on aluminium centred wheel with ball bearing. Wheel diameter 160mm, tread width 50mm, overall height 195mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 400kg and 160kg at 4kph REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC \*\* FOR INTERNAL TOWING USE ONLY \*\*



Diameter (mm)	160
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	195
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80/75
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	7
Fork Thickness (mm)	6
Swivel Radius (mm)	156
Load Capacity (kg)	400
Tread (mm)	50

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

