

## Elastic Rubber on Aluminium Plate Swivel Castor Brake 100mm 250kg Load

**Product code: BZKL100ERBJSWB**

Fabricated swivel castor with a top plate fixing fitted with a black 65 shore A elastic rubber on aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 100mm, tread width 50mm, overall height 140mm, top plate 138mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 250kg.



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 100  |
| Fixing Option            | Plate  |
| Castor Type              | Swivel with Total Lock Brake                       |
| Bearing Type             | Ball   |
| Height (mm)              | 140  |
| Plate Size (mm)          | 138 x 110  |
| Hole Centres (mm)        | 105 x 80   |
| To Suit Fixing Bolt (mm) | 10   |
| Wheel Material           | Rubber on Aluminium                                |
| Colour / Shore Hardness  | Black Elastic Rubber on Aluminium Rim / 65 Shore A |
| Temperature Resistance   | -30 °C TO +80 °C                                   |
| Top Plate Thickness (mm) | 7.5  |
| Fork Thickness (mm)      | 6  |
| Swivel Radius (mm)       | 100  |
| Load Capacity (kg)       | 250  |
| Tread (mm)               | 50   |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729