

## Elastic Rubber on Aluminium Plate Swivel Castor Brake 200mm 500kg Load

**Product code: BZSAB200ERBJSWB**



Fabricated zinc plated swivel castor with plate fixing fitted with a black high elastic natural 65 shore A rubber aluminium centred wheel with ball bearings and a total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 250mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 500kg at 4kph and 200kg at 10kph REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC \*\* FOR INTERNAL AND EXTERNAL TOWING USE \*\*

|                          |  |
|--------------------------|--|
| Diameter (mm)            | 200  |
| Fixing Option            | Plate  |
| Castor Type              | Swivel with Total Lock Brake                       |
| Bearing Type             | Ball   |
| Height (mm)              | 250  |
| Plate Size (mm)          | 138 x 110  |
| Hole Centres (mm)        | 105 x 80   |
| To Suit Fixing Bolt (mm) | 10   |
| Wheel Material           | Rubber on Aluminium                                |
| Colour / Shore Hardness  | Black Elastic Rubber on Aluminium Rim / 65 Shore A |
| Temperature Resistance   | -30 °C TO +80 °C                                   |
| Top Plate Thickness (mm) | 8  |
| Fork Thickness (mm)      | 6  |
| Swivel Radius (mm)       | 155  |
| Load Capacity (kg)       | 500  |
| Tread (mm)               | 50   |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

