

Elastic Rubber on Aluminium Plate Swivel Castor Brake Locking Castor 80mm 180kg Load

Product code: JAZ80ERBJSWB

Zinc plated box jacking unit with side fitting plate and a 75mm lift fitted with a 80mm zinc plated swivel pressed steel castor with a 65 shore A black elastic rubber tyre on aluminium centred wheel with ball bearings and total lock brake with a load capacity of 180kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. One extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. Please refer to the BIL catalogue or request a drawing. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



Diameter (mm)	80
Castor Height (mm)	110
Castor Type	Swivel with Total Lock Brake
Swivel Radius (mm)	125
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Load Capacity (kg)	180
Tread (mm)	40
Height (mm)	348 / 423
Lifting Stroke (mm)	75