

Elastic Speed Rubber on Cast Iron Plate Fixed Castor 150mm 400kg Load

Product code: BZSPHF150CUBJ

Pressed steel fixed bracket with a top plate fixing fitted with a black high elastic natural 65 shore A rubber tyre wheel aluminium centre with ball bearings. Wheel diameter 150mm, tread width 50mm, overall height 190mm, top plate 135mm x 114mm, hole centres 105mm x 80/75mm. Load capacity 400kg at 4kph, 160kg at 10kph, 150kg at 16kph and 140kg at 20kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC ****INTERNAL TOWING USE ONLY****



Diameter (mm)	150
Castor Type	Fixed
Fixing Option	Plate
Height (mm)	190
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 65 Shore A
Temperature Resistance	-20 °C TO +60 °C
Bearing Type	Ball
Load Capacity (kg)	400
Tread (mm)	50
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80/75
Top Plate Thickness (mm)	5
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	10

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

