

Elastic Speed Rubber Plate Swivel Braked Castor 457mm 2000kg Load

Product code: 2BZSAB450MKCUBJDBR



POA Fabricated zinc plated twin wheel swivel braked castor with plate fixing fitted with 2x black elastic rubber tyred on a steel disc centred wheel with ball bearings. Wheel diameter 457mm, tread width 2 x 93mm, overall height 554mm, plate size 270mm x 250mm, hole centre's 230mm x 220mm. Load capacity 2000kg at 4kph, 1100kg at 10kph and 900kg at 16kph
****MANUFACTURED TO ORDER****

Diameter (mm)	450
Fixing Option	Plate
Castor Type	Swivel with Wheel Brake
Bearing Type	Ball
Plate Size (mm)	270 x 250
Hole Centres (mm)	230 x 220
Height (mm)	554
Swivel Radius (mm)	304
To Suit Fixing Bolt (mm)	16
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	"-20 °C TO +60 °C
Tread (mm)	2 x 122
Load Capacity (kg)	2000

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

