

Elastic Speed Rubber Plate Swivel Castor 250mm 900kg Load

Product code: 2BZSAB250MKCUBJ

POA Fabricated zinc plated twin wheel swivel castor with plate fixing fitted 2x black elastic rubber tyred on a steel disc centred wheel with ball bearings. Wheel diameter 250mm, tread width 2 x 84mm, overall height 310mm, plate size 135mm x 110mm, hole centre's 105mm x 80mm. Load capacity 900kg at 4kph, 500kg at 10kph and 400kg at 16kph ****MANUFACTURED TO ORDER****



Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80
Height (mm)	310
Swivel Radius (mm)	200
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	"-20 °C TO +60 °C
Tread (mm)	2 x 84
Load Capacity (kg)	900

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

