

Electrically Conductive Polyurethane Nylon Swivel Castor Brake Bolthole 100mm 110kg

Product code: SSMM100PNBECBH12SWB

Grade 304 Pressed stainless steel swivel castor with bolt hole fixing fitted with a black electrically conductive polyurethane tyre nylon centred wheel with stainless steel roller bearings and swivel wheel brake. Wheel diameter 100mm, tread width 30mm, overall height 128mm, 12mm bolt hole. Load capacity 110kg. Conductive offers a resistance $R < 10000 \text{ Ohm}$



| | |
|--------------------------|--|
| Diameter (mm) | 100 |
| Fixing Option | Bolt Hole |
| Castor Type | Swivel with Total Lock Brake |
| Height (mm) | 128 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Black Polyurethane on Nylon Rim / 97 Shore A |
| Bearing Type | Roller |
| Tread (mm) | 30 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 12 |
| Load Capacity (kg) | 120 |
| Temperature Resistance | -20 °C TO +80 °C |
| Head Dia (mm) | 76 |
| Swivel Radius (mm) | 118 |