

## Electrically Conductive Polyurethane Nylon Swivel Castor Brake Bolthole 125mm 150kg

**Product code: SSMM125PNBECBH12SWB**



Grade 304 Pressed stainless steel swivel castor with a 12mm bolt hole fitted with a black electrically conductive polyurethane on nylon wheel with roller bearing and a total lock brake. Wheel diameter 125mm, tread width 35mm, overall height 155mm. Load capacity 150kg Conductive offers a resistance  $R < 10000 \text{ Ohm}$ .

|                          |  |
|--------------------------|--|
| Diameter (mm)            | 125  |
| Fixing Option            | Bolt Hole                                    |
| Castor Type              | Swivel with Total Lock Brake                 |
| Height (mm)              | 155  |
| Wheel Material           | Polyurethane on Nylon                        |
| Colour / Shore Hardness  | Black Polyurethane on Nylon Rim / 97 Shore A |
| Bearing Type             | Roller                                       |
| Tread (mm)               | 35   |
| Fork Thickness (mm)      | 2  |
| To Suit Fixing Bolt (mm) | 12   |
| Load Capacity (kg)       | 150  |
| Temperature Resistance   | -20 °C TO +80 °C                             |
| Head Dia (mm)            | 76   |
| Swivel Radius (mm)       | 123  |