

Electrically Conductive Polyurethane Nylon Swivel Castor Plate 125mm 150kg

Product code: SSMM125PNBEC



Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a black electrically conductive polyurethane on nylon wheel with roller bearing. Wheel diameter 125mm, tread width 35mm, overall height 155mm, top plate 105mm x 85mm, hole centres 80mm x 60mm. Load capacity 150kg Conductive offers a resistance $R < 10000 \text{ Ohm}$.

| | |
|--------------------------|--|
| Diameter (mm) | 125 |
| Fixing Option | Plate |
| Castor Type | Swivel |
| Height (mm) | 155 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Black Polyurethane on Nylon Rim / 97 Shore A |
| Bearing Type | Roller |
| Tread (mm) | 35 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |
| Load Capacity (kg) | 150 |
| Temperature Resistance | -20 °C TO +80 °C |
| Plate Size (mm) | 105 X 85 |
| Hole Centres (mm) | 80 X 60 |
| Top Plate Thickness (mm) | 2 |
| Swivel Radius (mm) | 95 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

