

## Electrically Conductive Rubber Bolt Hole Fixed Castor 75mm 60kg Load

**Product code: SSRAF75GRECBH10**

Grade 304 Pressed stainless steel fixed castor with a 10mm bolt hole fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with a plain bore. Wheel diameter 75mm, tread width 24mm, overall height 101mm. plate size 60mm x 60mm, hole centres 49.5mm x 49.5mm or 42.5mm x 42.5mm Load capacity 60kg. Conductive offers a resistance R<10\_\_ **\*\*MANUFACTURED TO ORDER\*\***



Diameter (mm)	75
Fixing Option	Bolt Hole
Castor Type	Fixed
Height (mm)	101
Wheel Material	Rubber on Polypropylene
Colour / Shore Hardness	Grey Rubber on Polypropylene Rim / 85 Shore A
Bearing Type	Plain
Tread (mm)	24
Fork Thickness (mm)	1.8
To Suit Fixing Bolt (mm)	10
Load Capacity (kg)	60
Temperature Resistance	-15 °C TO +80 °C
Head Dia (mm)	50

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

