

Electrically Conductive Rubber Bolt Hole Swivel Castor Brake 80mm 100kg

Product code: SSMM80RNBJECBH12SWB



Grade 304 stainless steel swivel castor with a 12mm bolt hole fitted with a 65 shore A black elastic electrically conductive rubber wheel on a black nylon centre with a ball bearing (NB the ball bearing is not stainless steel) and a total lock brake. Wheel diameter 80mm, tread width 35mm, overall height 105mm, Load capacity 100kg. Conductivity range is 10^3 ohm to 10^4 ohm

Diameter (mm)	80
Fixing Option	Bolt Hole
Castor Type	Swivel with Total Lock Brake
Height (mm)	105
Wheel Material	Rubber on Nylon
Colour / Shore Hardness	Black Elastic Rubber on Nylon Rim / 65 Shore A
Bearing Type	Ball
Tread (mm)	35
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	12
Load Capacity (kg)	100
Temperature Resistance	-20 °C TO +60 °C
Head Dia (mm)	76
Swivel Radius (mm)	111

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

