

Electrically Conductive Rubber Plate Fixed Castor 75mm 70kg Load

Product code: SSMF75GREC

Stainless steel fixed castor with a top plate fixing fitted with a grey electrically conductive tyre on a black polypropylene centred wheel with plain bore. Wheel diameter 75mm, tread width 32mm, overall height 109mm, top plate 90mm x 70mm, hole centres 75mm x 56mm or 64mm x 44mm. Load capacity 70kg. Conductive offers a resistance $R < 10 \Omega$



| | |
|--------------------------|---|
| Diameter (mm) | 75 |
| Fixing Option | Plate |
| Castor Type | Fixed |
| Height (mm) | 109 |
| Wheel Material | Rubber on Polypropylene |
| Colour / Shore Hardness | Grey Rubber on Polypropylene Rim / 85 Shore A |
| Bearing Type | Plain |
| Tread (mm) | 32 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |
| Load Capacity (kg) | 90 |
| Temperature Resistance | -15 °C TO +80 °C |
| Plate Size (mm) | 90 x 70 |
| Hole Centres (mm) | 75/64 x 56/44 |
| Top Plate Thickness (mm) | 2 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

