


Electrically Conductive Rubber Plate Swivel Castor 125mm 250kg Load

Product code: BZH125RNBJEC

Pressd steel swivel castor with a top plate fixing fitted with a 65 shore A black elastic electrically conductive rubber wheel on a black nylon centre with a ball bearing. Wheel diameter 125mm, tread width 36mm, overall height 155mm, top plate 105mm x 86mm, hole centres 80mm x 60mm Load capacity 250kg. Conductivity range is 10^3 ohm to 10^4 ohm



| | |
|--------------------------|---------------------------------------|
| Diameter (mm) | 125 |
| Castor Type | Swivel |
| Fixing Option | Plate |
| Height (mm) | 155 |
| Wheel Material | Rubber on Nylon |
| Colour / Shore Hardness | Blue Rubber on Nylon Rim / 75 Shore A |
| Temperature Resistance | -20 °C TO +60 °C |
| Bearing Type | Ball |
| Load Capacity (kg) | 250 |
| Tread (mm) | 36 |
| Swivel Radius (mm) | 104 |
| Plate Size (mm) | 105 x 86 |
| Hole Centres (mm) | 80 X 60 |
| Top Plate Thickness (mm) | 4 |
| Fork Thickness (mm) | 4 |
| To Suit Fixing Bolt (mm) | 8 |