

## Ergonomic Polyurethane Plate Fixed Castor 200mm 1500kg Load

**Product code: 2BZKF200RPTABJ**

Twin wheeled fabricated fixed castor with a top plate fixing fitted with 2 ergonomic polyurethane tyred aluminium centred wheels with ball bearings. Wheel diameter 2 x 200mm, tread width 2 x 50mm, overall height 250mm, top plate 175mm x 150mm hole centres 105mm x 80mm or 121mm x 59mm. Load capacity 1500kg.



Diameter (mm)	200
Fixing Option	Plate
Castor Type	Fixed
Bearing Type	Ball
Plate Size (mm)	175 x 150
Hole Centres (mm)	105/121 x 80/59
Height (mm)	250
To Suit Fixing Bolt (mm)	12
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Ergonomic Polyurethane on Aluminium Rim / 95 Shore A
Temperature Resistance	&quot;-20 °C TO +80 °C
Tread (mm)	2 x 50
Load Capacity (kg)	1500
Top Plate Thickness (mm)	7.5
Fork Thickness (mm)	6

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

