

## Ergonomic Polyurethane Plate Swivel Castor Brake 125mm 450kg Load

**Product code: BZH125SRPTABJSWB**



Pressed steel swivel castor with a top plate fixing fitted with a 85 shore A green ergonomic polyurethane tyre on a aluminium centred wheel with a ball bearing and total lock brake. Wheel diameter 125mm, tread width 50mm, overall height 156mm, top plate 105mm x 86mm, hole centres 80mm x 60mm. Load capacity 450kg.

Diameter (mm)	125
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	155
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Green Ergonomic Polyurethane on Aluminium Rim / 85 Shore A
Temperature Resistance	-20 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	450
Tread (mm)	50
Swivel Radius (mm)	125
Plate Size (mm)	105 x 86
Hole Centres (mm)	80 X 60
Top Plate Thickness (mm)	4
Fork Thickness (mm)	4
To Suit Fixing Bolt (mm)	8

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

