

## Ergonomic Polyurethane Plate Swivel Castor Brake 150mm 575kg Load

**Product code: BZMJ150RPTABJSWB**

Fabricated white zinc ROHS plated swivel castor with a top plate fixing fitted with a round profile polyurethane on aluminium centred wheel with ball bearings and a total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 190mm, top plate 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 575kg.



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 150  |
| Fixing Option            | Plate  |
| Castor Type              | Swivel with Total Lock Brake                               |
| Bearing Type             | Ball   |
| Height (mm)              | 190  |
| Plate Size (mm)          | 138 x 110  |
| Hole Centres (mm)        | 105 x 80/75  |
| To Suit Fixing Bolt (mm) | 10   |
| Wheel Material           | Polyurethane on Aluminium                                  |
| Colour / Shore Hardness  | Brown Ergonomic Polyurethane on Aluminium Rim / 95 Shore A |
| Temperature Resistance   | -20 °C TO +80 °C   |
| Top Plate Thickness (mm) | 7  |
| Fork Thickness (mm)      | 6  |
| Swivel Radius (mm)       | 145  |
| Load Capacity (kg)       | 575  |
| Tread (mm)               | 50   |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

