

Grey Soft Elastic Rubber Plate Swivel Castor Brake 125mm 200kg Load

Product code: SSMM125SRERGBJSWB



Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a grey high elastic natural 55 shore A round profile rubber tyre aluminium centred wheel with stainless steel ball bearings. Wheel diameter 125mm, tread width 40mm, overall height 155mm, top plate 105 x 85mm, hole centres 80mm x 60mm. Load capacity 200kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC,

Diameter (mm)	125
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Height (mm)	155
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Grey Ergonomic Rubber on Aluminium Rim / 55 Shore A
Bearing Type	Ball
Tread (mm)	40
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	8
Load Capacity (kg)	90
Temperature Resistance	-30 °C TO +80 °C
Plate Size (mm)	105 X 85
Hole Centres (mm)	80 X 60
Top Plate Thickness (mm)	2
Swivel Radius (mm)	123

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

