

## Pneumatic 400mm Roller Bearing Wheel 200kg Load

**Product code: BZWPMR400204R/E**

Black pneumatic tyre on welded grey steel disc centre rim with a roller bearing bore (sorry no grease nipple). Fitted with a 4 ply ribbed tread patterned tyre. Wheel diameter 400mm, tread width 100mm, hub 75mm, bore 20mm. Load capacity 200kg at 4KPH please refer to the BIL catalogue regarding load capacity on tyre wall stating different load capacity, REACH COMPLIANT. If considering foam filling please take advise from the BIL Technical department or consider the BIL puncture proof range. for non-towing applications please note we manufacture to order and therefore a 24 hour delivery may not be possible.



|                         |  |
|-------------------------|--|
| Wheel Material          | Pneumatic tyre on Pressed Steel            |
| Diameter (mm)           | 400  |
| Load Capacity (kg)      | 200  |
| Bearing Type            | Roller                                     |
| Bore Size (mm)          | 20   |
| Tread (mm)              | 100  |
| Hub Width (mm)          | 75   |
| Colour / Shore Hardness | Black Pneumatic Tyre on Steel Rims / 4 Ply |
| Temperature Resistance  | -10 °C TO +60 °C                           |

## BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

