

Pneumatic wheel Plate Swivel Castor 300mm 155kg Load

Product code: BZFPC300PBJ

Fabricated swivel castor with a top plate fixing fitted with a 4 ply black diamond pattern pneumatic tyre with a red polypropylene centre and ball bearing. Wheel diameter 300, tread width 90mm, overall height 338mm, plate size 115mm x 105mm, hole centres 92mm x 67 or 76mm x 76mm. Load capacity 155kg.at max speed 4KPH, for non-towing applications please note we manufacture to order and therefore a 24 hour delivery may not be possible.



Diameter (mm)	300
Height (mm)	338
Plate Size (mm)	115 x 105
Hole Centres (mm)	76/92 x 76/67
Bearing Type	Ball
Load Capacity (kg)	155
Fixing Option	Plate
Castor Type	Swivel
Wheel Material	Pneumatic Wheels
Colour / Shore Hardness	Black Pneumatic Tyre on Polypropylene Rims / 4 Ply
Ply Rating	4
Swivel Radius (mm)	210
Top Plate Thickness (mm)	5
To Suit Fixing Bolt (mm)	10
Fork Thickness (mm)	5
Temperature Resistance	-10 °C TO +60 °C

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729