

## Polyurethane Aluminium Plate Swivel Castor Brake 160mm 500kg Load

**Product code: BZP160PABJSWB**

Pressed steel swivel castor with a flat plate fixing fitted with a brown polyurethane tyred on aluminium centred wheel with a ball bearing and total lock brake. Wheel diameter 160mm, tread width 50mm, overall height 199mm, plate size 135mm x 110mm, hole centres 105mm x 80mm. Load capacity 500kg.



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 160  |
| Castor Type              | Swivel with Total Lock Brake                     |
| Fixing Option            | Plate  |
| Height (mm)              | 199  |
| Wheel Material           | Polyurethane on Aluminium                        |
| Colour / Shore Hardness  | Brown Polyurethane on Aluminium Rim / 93 Shore A |
| Temperature Resistance   | -20 °C TO +70 °C                                 |
| Bearing Type             | Ball   |
| Load Capacity (kg)       | 500  |
| Tread (mm)               | 50   |
| Swivel Radius (mm)       | 150  |
| Plate Size (mm)          | 135 x 110  |
| Hole Centres (mm)        | 105 x 80   |
| Top Plate Thickness (mm) | 6  |
| Fork Thickness (mm)      | 4  |
| To Suit Fixing Bolt (mm) | 12   |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

