

Polyurethane Aluminium Plate Swivel Castor Brake 200mm 350kg Load

Product code: BZMM200PABJSWB

Pressed steel swivel castor with a top plate fixing fitted with a brown polyurethane tyred aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 235mm, top plate 140mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 350kg.



| | |
|--------------------------|--|
| Diameter (mm) | 200 |
| Castor Type | Swivel with Total Lock Brake |
| Fixing Option | Plate |
| Height (mm) | 235 |
| Wheel Material | Polyurethane on Aluminium |
| Colour / Shore Hardness | Brown Polyurethane on Aluminium Rim / 93 Shore A |
| Temperature Resistance | -20 °C TO +70 °C |
| Bearing Type | Ball |
| Load Capacity (kg) | 350 |
| Tread (mm) | 50 |
| Swivel Radius (mm) | 185 |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80 |
| Top Plate Thickness (mm) | 3 |
| Fork Thickness (mm) | 3 |
| To Suit Fixing Bolt (mm) | 10 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

