

Polyurethane Cast Iron Plate Swivel Castor 150mm 750kg Load

Product code: BZQ150PTBJ

Fabricated swivel castors with a top plate fixing fitted with a polyurethane tyred cast iron centred wheel with ball bearings. Wheel diameter 150mm, tread width 50mm, overall height 212mm, top plate 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 750kg.



| | |
|--------------------------|--|
| Diameter (mm) | 150 |
| Fixing Option | Plate |
| Castor Type | Swivel |
| Bearing Type | Ball |
| Height (mm) | 212 |
| Plate Size (mm) | 170 X 140 |
| Hole Centres (mm) | 140 X 105 |
| To Suit Fixing Bolt (mm) | 14 |
| Wheel Material | Polyurethane on Cast Iron |
| Colour / Shore Hardness | Brown Polyurethane on Cast Iron Rim / 94 Shore A |
| Temperature Resistance | -20 °C TO +80 °C |
| Top Plate Thickness (mm) | 12 |
| Fork Thickness (mm) | 10 |
| Swivel Radius (mm) | 128 |
| Load Capacity (kg) | 750 |
| Tread (mm) | 50 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

