

Polyurethane Cast Iron Plate Swivel Castor 200mm 2600kg Load

Product code: JAZHD2X200PTBJWT



Side plate fixing fabricated zinc plated jacking unit fitted with a twin wheel 200mm swivel castor with 2 x polyurethane on cast iron centred ball bearing wheels, Tread width 60mm x 2 plate size 200mm x 110mm, hole centres 135mm x 80mm, height 681m/831mm, maximum lift is 150mm. Load capacity 2600kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. for other dimensions please refer to the BIL catalogue or request a drawing. When jacked up to the height please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. **DO NOT OVERWIND** Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)

Diameter (mm)	200
Castor Height (mm)	264
Castor Type	Swivel
Swivel Radius (mm)	185
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	16
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Temperature Resistance	-20 °C TO +80 °C
Load Capacity (kg)	2600
Tread (mm)	2 x 60
Height (mm)	681 / 831
Lifting Stroke (mm)	150
Handle Option	Fixed