

Polyurethane Cast Iron Plate Swivel Castor Brake Locking Castor 125mm 400kg Load

Product code: JAZHS125PTBJSWB

Side winding jacking castor unit with a maximum lift of 200mm. Fitted with a fabricated swivel castor with a top plate fixing. Includes a brown, polyurethane-tyred cast iron centred wheel with ball bearings and a total lock brake. Wheel diameter 125mm, tread width 40mm, maximum load capacity 400kg for the complete unit. Note 1) Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. For other dimensions please see below, or the BIL catalogue or request a drawing. Note 2) When jacked up to height please be aware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. Note 3) This castor has a brake - ensure all brakes are in the off position before moving. Note 4) DO NOT OVERWIND handle excessively. Overwinding (ie more than needed) will cause the pin in the gearbox to shear. (This is a safety precaution against overloading the unit).



Diameter (mm)	125
Castor Height (mm)	165
Castor Type	Swivel with Total Lock Brake
Swivel Radius (mm)	101
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Temperature Resistance	-20 °C TO +80 °C
Load Capacity (kg)	400
Tread (mm)	40
Height (mm)	572 / 772
Lifting Stroke (mm)	200
Handle Option	Fixed