

Polyurethane Cast Iron Plate Swivel Castor Brake Locking Castor 80mm 250kg Load

Product code: JAZ80PTBJSWB



Zinc plated box jacking unit with side fitting plate and a 75mm lift fitted with a 80mm white zinc plated swivel pressed steel castor with a polyurethane tyred cast iron centred ball bearing wheel and total lock brake, with a load capacity of 200kg
 Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. 1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. Please refer to the BIL catalogue or request a drawing

| | |
|--------------------------|--|
| Diameter (mm) | 80 |
| Castor Height (mm) | 110 |
| Castor Type | Swivel with Total Lock Brake |
| Swivel Radius (mm) | 125 |
| Fixing Option | Plate |
| Bearing Type | Ball |
| To Suit Fixing Bolt (mm) | 14 |
| Wheel Material | Polyurethane on Cast Iron |
| Colour / Shore Hardness | Brown Polyurethane on Cast Iron Rim / 94 Shore A |
| Temperature Resistance | -20 °C TO +80 °C |
| Load Capacity (kg) | 250 |
| Tread (mm) | 36 |
| Height (mm) | 348 / 423 |
| Lifting Stroke (mm) | 75 |