

Polyurethane Nylon Plate Swivel Castor 150mm 250kg Load

Product code: JAZ150NP

Zinc plated box jacking unit with side fitting plate and a 75mm lift fitted with a 150mm white zinc plated swivel pressed steel castor with a red polyurethane tyred white nylon centred wheel with plain bore with a load capacity of 250kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units.1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. Please refer to the BIL catalogue or request a drawing



Diameter (mm)	150
Castor Height (mm)	188
Castor Type	Swivel
Swivel Radius (mm)	128
Fixing Option	Plate
To Suit Fixing Bolt (mm)	14
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane on Nylon Rim / 96 Shore A
Temperature Resistance	-20 °C TO +70 °C
Load Capacity (kg)	250
Tread (mm)	40
Height (mm)	426 / 501
Lifting Stroke (mm)	75
Bearing Type	Plain

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

