

Polyurethane Nylon Plate Swivel Castor Brake 100mm 150kg Load

Product code: SSMM100NPSWB

Grade 304 Pressed stainless steel swivel castor with top plate fixing fitted with a polyurethane tyre nylon centred wheel with plain bore and swivel wheel brake. Wheel diameter 100mm, tread width 30mm, overall height 128mm, top plate 105mm x 85mm, hole centres 80mm x 60mm. Load capacity 150kg.



| | |
|--------------------------|--|
| Diameter (mm) | 100 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Height (mm) | 128 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Bearing Type | Plain |
| Tread (mm) | 30 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |
| Load Capacity (kg) | 170 |
| Temperature Resistance | -20 °C TO +70 °C |
| Plate Size (mm) | 105 X 85 |
| Hole Centres (mm) | 80 X 60 |
| Top Plate Thickness (mm) | 2.5 |
| Swivel Radius (mm) | 118 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

