

## Polyurethane Nylon Plate Swivel Castor Brake 125mm 300kg Load

**Product code: BZEH125NPSWB**

Pressed steel swivel castor with top plate fixing fitted with a red polyurethane tyred on a white nylon centred wheel with a plain bore and a total lock brake. Wheel diameter 125mm, tread width 35mm, overall height 155mm, top plate 105mm x 86mm, hole centres 80mm x 60mm. Load capacity 300kg.



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 125  |
| Castor Type              | Swivel with Total Lock Brake               |
| Fixing Option            | Plate                                      |
| Height (mm)              | 155  |
| Wheel Material           | Polyurethane on Nylon                      |
| Colour / Shore Hardness  | Red Polyurethane on Nylon Rim / 96 Shore A |
| Temperature Resistance   | -20 °C TO +70 °C                           |
| Bearing Type             | Plain                                      |
| Load Capacity (kg)       | 300  |
| Tread (mm)               | 35   |
| Swivel Radius (mm)       | 120  |
| Plate Size (mm)          | 105 x 86                                   |
| Hole Centres (mm)        | 80 X 60                                    |
| Top Plate Thickness (mm) | 3  |
| Fork Thickness (mm)      | 3  |
| To Suit Fixing Bolt (mm) | 8  |