

Polyurethane Nylon Plate Swivel Castor Brake 150mm 500kg Load

Product code: BZMJ150NPBSWB



Fabricated white zinc ROHS plated swivel castor with a top plate fixing fitted with a red polyurethane on white nylon centred wheel with roller bearings and total lock brake. Wheel diameter 150mm, tread width 40mm, overall height 190mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 500kg.

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Roller
Height (mm)	190
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80/75
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane on Nylon Rim / 96 Shore A
Temperature Resistance	-20 °C TO +70 °C
Top Plate Thickness (mm)	7
Fork Thickness (mm)	6
Swivel Radius (mm)	145
Load Capacity (kg)	500
Tread (mm)	40

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

