

## Polyurethane Nylon Plate Swivel Castor Brake 160mm 350kg Load

**Product code: SSMM160PNBSWB**

Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a brown polyurethane tyred white nylon centred wheel with a roller bearing and total lock. Wheel diameter 160mm, tread width 40mm overall height 195mm, top plate 140mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 350kg.



Diameter (mm)	160
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Height (mm)	195
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Brown Polyurethane on Nylon Rim / 96 Shore A
Bearing Type	Roller
Tread (mm)	45
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	10
Load Capacity (kg)	400
Temperature Resistance	-20 °C TO +80 °C
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80
Top Plate Thickness (mm)	3
Swivel Radius (mm)	167

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

