

## Polyurethane Nylon Plate Swivel Castor Brake 200mm 400kg Load

**Product code: SSMM200NPSWB**

Grade 304 Pressed stainless steel swivel castor with a top plate fitted with a red polyurethane tyre on white nylon centred wheel with a plain bore and a total lock brake, 200mm wheel diameter, 48mm tread width, 235mm overall height, 135 x 110mm top plate, 105 x 80mm bolt holes, with a load capacity of 400kgs.



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 200  |
| Fixing Option            | Plate                                      |
| Castor Type              | Swivel with Total Lock Brake               |
| Height (mm)              | 235  |
| Wheel Material           | Polyurethane on Nylon                      |
| Colour / Shore Hardness  | Red Polyurethane on Nylon Rim / 96 Shore A |
| Bearing Type             | Plain                                      |
| Tread (mm)               | 48   |
| Fork Thickness (mm)      | 2.5  |
| To Suit Fixing Bolt (mm) | 10   |
| Load Capacity (kg)       | 400  |
| Temperature Resistance   | -20 °C TO +70 °C                           |
| Plate Size (mm)          | 135 x 110                                  |
| Hole Centres (mm)        | 105 x 80                                   |
| Top Plate Thickness (mm) | 3.5  |
| Swivel Radius (mm)       | 167  |