

## Polyurethane Nylon Plate Swivel Castor Brake 80mm 210kg Load

**Product code: SSEH80NPBSWB**

Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a red polyurethane tyred white nylon centred wheel with a roller bearing and a total lock brake. Wheel diameter 80mm, tread width 33mm, overall height 111mm, top plate 105mm x 86mm, hole centres 80mm x 60mm. Load capacity 210kg



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 80   |
| Fixing Option            | Plate                                      |
| Castor Type              | Swivel with Total Lock Brake               |
| Height (mm)              | 110  |
| Wheel Material           | Polyurethane on Nylon                      |
| Colour / Shore Hardness  | Red Polyurethane on Nylon Rim / 96 Shore A |
| Bearing Type             | Roller                                     |
| Tread (mm)               | 33   |
| Fork Thickness (mm)      | 3  |
| To Suit Fixing Bolt (mm) | 8  |
| Load Capacity (kg)       | 210  |
| Temperature Resistance   | -20 °C TO +70 °C                           |
| Plate Size (mm)          | 105 x 86                                   |
| Hole Centres (mm)        | 80 X 60                                    |
| Top Plate Thickness (mm) | 3  |
| Swivel Radius (mm)       | 116  |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

