

Polyurethane Plate Swivel Castor Brake Footguard 150mm 500kg load

Product code: BZPH150PTBJSWBFG

Pressed steel swivel castor with a top plate fixing fitted with a polyurethane tyre on cast iron centred wheel with ball bearings, total lock brake and footguard. Wheel diameter 150mm, tread width 50mm, overall height 190mm, top plate 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 500kg.



Height (mm)	190
Tread (mm)	50
To Suit Fixing Bolt (mm)	10
Bearing Type	Ball
Diameter (mm)	150
Wheel Material	Polyurethane on Cast Iron
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Load Capacity (kg)	500
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Swivel Radius (mm)	167
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80/75
Fork Thickness (mm)	4
Top Plate Thickness (mm)	4
Temperature Resistance	-20 °C TO +80 °C

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

