

Puncture Proof Polyurethane Plate Swivel Castor 260mm 100kg Load

Product code: BZPC260PPUD/LITE

Pressed steel swivel castor with a flat plate fixing fitted with a black puncture proof diamond pattern tyre on red polypropylene centred wheel with a plain bore. Wheel diameter 260mm, tread width 85mm, overall height 307mm, plate size 200mm x 160mm, hole centres 150mm x 115mm, Load capacity 100kg.



| | |
|--------------------------|--|
| Diameter (mm) | 260 |
| Castor Type | Swivel |
| Fixing Option | Plate |
| Plate Size (mm) | 200 X 160 |
| Height (mm) | 307 |
| Hole Centres (mm) | 150 x 115 |
| Swivel Radius (mm) | 215 |
| Tread (mm) | 85 |
| Temperature Resistance | -10 °C TO +60 °C |
| To Suit Fixing Bolt (mm) | 14 |
| Bearing Type | Plain |
| Wheel Material | Puncture Proof Wheels |
| Load Capacity (kg) | 100 |
| Colour / Shore Hardness | Black Puncture Proof Tyre on Polypropylene Rims / Low PU |
| Top Plate Thickness (mm) | 4 |
| Fork Thickness (mm) | 3 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

