

Puncture Proof Polyurethane Plate Swivel Castor 260mm 150kg Load

Product code: BZFPC260MPUBD

Fabricated swivel castor with a top plate fixing fitted with a black diamond pattern puncture proof tyre red steel disc centred wheel with roller bearing. Wheel diameter 260, tread width 85mm, overall height 318mm, plate size 115mm x 105mm, hole centres 92mm x 67mm or 76mm x 76mm. Load capacity 150kg.



Diameter (mm)	260
Castor Type	Swivel
Fixing Option	Plate
Plate Size (mm)	115 x 105
Height (mm)	318
Hole Centres (mm)	76/92 x 76/67
Swivel Radius (mm)	190
Tread (mm)	85
Temperature Resistance	-10 °C TO +60 °C
To Suit Fixing Bolt (mm)	10
Bearing Type	Roller
Wheel Material	Puncture Proof Wheels
Load Capacity (kg)	150
Colour / Shore Hardness	Black Puncture Proof Tyre on Steel Rims / High PU
Top Plate Thickness (mm)	5
Fork Thickness (mm)	7.5

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

