

Puncture Proof Polyurethane Plate Swivel Castor 300mm 150kg Load

Product code: BZFPC300MPUBJD

Fabricated swivel castor with a top plate fixing fitted with a black diamond pattern puncture proof tyre red polypropylene centred wheel with ball bearing. Wheel diameter 300mm, tread width 85mm, overall height 338mm, plate size 115mm x 105mm, hole centres 92mm x 67mm or 76mm x 76mm. Load capacity 150kg. Please note this is a red polypropylene rim



Diameter (mm)	300
Castor Type	Swivel
Fixing Option	Plate
Plate Size (mm)	115 x 105
Height (mm)	338
Hole Centres (mm)	76/92 x 76/67
Swivel Radius (mm)	210
Tread (mm)	90
Temperature Resistance	-10 °C TO +60 °C
To Suit Fixing Bolt (mm)	10
Bearing Type	Ball
Wheel Material	Puncture Proof Wheels
Load Capacity (kg)	150
Colour / Shore Hardness	Black Puncture Proof Tyre on Steel Rims / High PU
Top Plate Thickness (mm)	5
Fork Thickness (mm)	7.5

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729