

Puncture Proof Polyurethane Plate Swivel Castor Brake 260mm 100kg Load

Product code: BZFPC260PPUBDBK/LITE

Fabricated swivel castor with a top plate fixing fitted with a black diamond pattern puncture proof tyre red polypropylene centred wheel with roller bearing and a side fitting wheel brake. Wheel diameter 260, tread width 85mm, overall height 318mm, plate size 115mm x 105mm, hole centres 92mm x 67mm or 76mm x 76mm. Load capacity 100kg.



| | |
|--------------------------|--|
| Diameter (mm) | 260 |
| Castor Type | Swivel with Wheel Brake |
| Fixing Option | Plate |
| Plate Size (mm) | 115 x 105 |
| Height (mm) | 318 |
| Hole Centres (mm) | 76/92 x 76/67 |
| Swivel Radius (mm) | 205 |
| Tread (mm) | 85 |
| Temperature Resistance | -10 °C TO +60 °C |
| To Suit Fixing Bolt (mm) | 10 |
| Bearing Type | Roller |
| Wheel Material | Puncture Proof Wheels |
| Load Capacity (kg) | 100 |
| Colour / Shore Hardness | Black Puncture Proof Tyre on Polypropylene Rims / Low PU |
| Top Plate Thickness (mm) | 5 |
| Fork Thickness (mm) | 5 |